

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
17 March 2005 (17.03.2005)

PCT

(10) International Publication Number  
**WO 2005/024268 A1**

(51) International Patent Classification<sup>7</sup>: **F16G 11/12**,  
B65H 77/00, 59/14, B63B 21/04, B60P 7/06, E04H 15/32

(21) International Application Number:  
PCT/AU2004/001212

(22) International Filing Date:  
8 September 2004 (08.09.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
2003904860 8 September 2003 (08.09.2003) AU

(71) Applicant and

(72) Inventor: **THOMAS, Scott, Ronald** [NZ/AU]; 35 Gailey  
Street, Ashgrove, Queensland 4060 (AU).

(74) Agent: **FISHER ADAMS KELLY**; Level 13, AMP Place,  
10 Eagle Street, Brisbane, Queensland 4001 (AU).

(81) Designated States (*unless otherwise indicated, for every  
kind of national protection available*): AE, AG, AL, AM,

AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,  
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,  
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,  
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,  
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,  
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,  
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,  
ZW.


(84) Designated States (*unless otherwise indicated, for every  
kind of regional protection available*): ARIPO (BW, GH,  
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,  
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,  
FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,  
SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,  
GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

*For two-letter codes and other abbreviations, refer to the "Guid-  
ance Notes on Codes and Abbreviations" appearing at the begin-  
ning of each regular issue of the PCT Gazette.*

(54) Title: LINE TENSIONING DEVICE AND METHODS



(57) Abstract: A line tensioning device (10) comprising an elongated body (12) having a line locating region (13) and a hook (14) at a first end (16) of the elongated body, wherein the hook is adapted to maintain the line tensioning device in position after rotation of the device to achieve a desired tension in the line (22). The device comprises at least one aperture (18) through the elongated body and at least one locking means (24) in the form of a pivotally mounted, manually operated lever (26) for securing in position a line passing through one of the apertures (18).